

# STYLE 304

## ALL STAINLESS STEEL SERVICE SADDLES



### MATERIAL SPECIFICATIONS

**SHELLS:** Stainless steel per ASTM A240, type 304, passivated for corrosion resistance.

**BOLTS:** UNC rolled thread, 304 stainless steel.

**NUTS:** Stainless steel per ASTM A194, type 304.

**WASHERS:** Stainless steel type 304 and plastic lubricating washers.

**GASKET:** NBR per ASTM D2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

**TAPPED OUTLET:** Stainless steel per ASTM A240, type 304.



**NSF61  
CERTIFIED**

**MEETS  
AWWA C800**

304 SINGLE BOLT (not recommended for A/C pipe)						
NOM. PIPE SIZE	O.D. PIPE RANGE	LENGTH	BOLT SIZE	TAP		APPROX. WEIGHT EA. (lbs.)
				I.P. 1/2" - 1"	C.C. 3/4" OR 1"	
2"	2.13 2.38	4"	1/2"	\$140.91	\$140.91	2 #
2 1/2"	2.63 - 2.88	4"	1/2"	144.72	144.72	2 #
3"	3.00 - 3.25	4"	1/2"	147.55	147.55	2 #
	3.25 - 3.50					
	3.50 - 3.75					
	3.75 - 4.00					
4"	4.00 - 4.30	4"	1/2"	172.66	172.66	3 #
	4.50 - 4.80					
	4.80 - 5.20					
5"	5.20 - 5.60	4"	1/2"	174.83	174.83	3 #
	5.60 - 6.00					
6"	6.00 - 6.40	4"	5/8"	237.85	237.85	4 #
	6.50 - 6.90					
	6.90 - 7.30					
8"	8.00 - 8.40	4"	5/8"	240.89	240.89	5 #
	8.63 - 9.05					
	9.05 - 9.45					

For easiest installation, choose the saddle with your pipe O.D. closest to the bottom of the range.

Other O.D.s available P.O.A.

**TO ORDER:** Use upper range when ordering. Add tap size. Be specific when ordering.

Tapped outlet products are NO CANCEL/NO RETURN items.

**EXAMPLE:** 304 - 4.80 x 3/4" I.P.