

# STYLE 305

## ALL STAINLESS STEEL SERVICE SADDLES



### MATERIAL SPECIFICATIONS

**SHELLS:** Stainless steel per ASTM A240, type 304, passivated for corrosion resistance.

**BOLTS:** UNC rolled thread, 304 stainless steel.

**NUTS:** Stainless steel type 304.

**WASHERS:** Stainless steel per ASTM A240, type 304 and plastic lubricating washers.

**GASKET:** Pad with O-ring gasket. NBR per ASTM D2000 MBC 610, compounded for water and sewer service. Other compounds available on request. Pipe sizes <15.00 with outlets <2 1/2" use Pad with O-ring gasket. All other sizes use ring gasket with wire reinforcement.

**TAPPED OUTLET:** Stainless steel per ASTM A240, type 304.

**Not recommended for concrete cylinder pipe.**



Certified to  
NSF/ANSI 61 & 372



MEETS  
AWWA C800

305 MULTI BOLT (can be used on A/C pipe)						
NOM. PIPE SIZE	O.D. PIPE RANGE	8" WIDE			10" WIDE	APPROX. WEIGHT (lbs.)
		I.P. 1/2"	I.P. or C.C. 3/4", 1"	I.P. or C.C. 1 1/4", 1 1/2", 2"	FIP or MIP 2 1/2", 3"	
10" - 12"	10.00 - 10.80	\$433.95 (4 bolts)	\$433.95 (4 bolts)	\$495.24 (4 bolts)	\$1,126.57 (6 bolts)	14 #
	10.80 - 11.60					
	12.00 - 12.80					
	12.80 - 13.60					
	13.70 - 14.50					
14" - 16"	15.00 - 15.80	551.15 (4 bolts)	551.15 (4 bolts)	633.92 (4 bolts)	1,265.12 (6 bolts)	16 #
	15.90 - 16.70					
	16.70 - 17.50					
16" - 18"	17.30 - 18.10	641.21 (4 bolts)	641.21 (4 bolts)	733.43 (6 bolts)	1,364.77 (6 bolts)	17 #
	18.15 - 18.95					
	19.00 - 19.80					
18" - 20"	19.30 - 20.10	719.85 (4 bolts)	719.85 (4 bolts)	960.04 (6 bolts)	1,591.37 (6 bolts)	18 #
	20.00 - 20.80					
	21.10 - 21.90					
22" - 24"	22.00 - 22.80	760.14 (6 bolts)	760.14 (6 bolts)	999.93 (6 bolts)	1,603.21 (6 bolts)	19 #
	23.20 - 24.00					
	24.60 - 25.40					
	25.70 - 26.50					

Other O.D.s available P.O.A.

**TO ORDER:** Use upper range when ordering. Add tap size. Be specific when ordering.

Tapped outlet products are NO CANCEL/NO RETURN items.

**EXAMPLE:** 305 - 10.80 x 3/4" I.P.