

305-H AND 306-H

ALL STAINLESS STEEL SERVICE SADDLES



HDPE

FOR HIGH DENSITY POLYETHYLENE PIPE

MATERIAL SPECIFICATIONS

SHELLS: Stainless steel per ASTM A240, type 304, passivated for corrosion resistance.

BOLTS: UNC rolled thread, 304 stainless steel.

NUTS: Stainless steel per ASTM A194, type 304. Coated to prevent galling.


WASHERS: Flat washers are stainless steel, type 304; spring washers are special "spring" grade of stainless steel and plastic lubricating washers.

GASKET: NBR per ASTM D2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

TAPPED OUTLET: Stainless steel per ASTM A240, type 304.



305-H SADDLE



306-H SADDLE

NSF 61/372 Certified.

For above-ground HDPE applications, contact Romac's Engineering Department at 1-800-426-9341.

Products and prices listed below are standard Romac sizes. For information on other sizes, contact Romac's Engineering Department.

For important technical information on HDPE pipe, see Page 9-1 & Page 9-2.

"306-H" SADDLE

NOM. PIPE SIZE	OUTSIDE DIAMETER	TAP	I.P.	C.C.	WEIGHT (lbs.)
2"	2.13	½", ¾", 1"	214.60	214.60	2 #
	2.38				
3"	3.50	½", ¾", 1"	410.24	410.24	3 #
		1 ¼"	471.23	471.23	
		1 ½"	471.23	471.23	
		2"	471.23	NA	
4"	4.50 4.80	½", ¾", 1"	421.26	421.26	4 #
		1 ¼"	471.23	471.23	
		1 ½"	471.23	471.23	
		2"	471.23	471.23	
5"	5.56	½", ¾", 1"	441.76	441.76	4 #
		1 ¼"	516.17	516.17	
		1 ½", 2"	516.17	516.17	
6"	6.63 6.90	½", ¾", 1"	492.31	492.31	4 #
		1 ¼"	527.29	527.29	
		1 ½", 2"	527.29	527.29	
8"	8.63 9.05	½", ¾", 1"	530.39	530.39	6 #
		1 ¼"	575.77	575.77	
		1 ½", 2"	575.77	575.77	

"305-H" SADDLE

NOM. PIPE SIZE	OUTSIDE DIAMETER	I.P. or C.C. ½", ¾", 1"	I.P. or C.C.		WEIGHT (lbs.)
			1¼", 1½", 2"	FIP or MIP 2½", 3"	
10"	10.75	\$753.91	\$823.51	\$1,671.09	14#
	11.10				
12"	12.75	753.91	823.51	1,671.09	14#
	13.20				

305-H

8" wide with four 5/8" bolts.

306-H

(A) 2" through 5" nominal sizes with small (½", ¾", or 1") taps are 6" long with two 1/2" bolts.

(B) 6" through 8" sizes with small (½", ¾", or 1") taps are 6" long with two 5/8" bolts.

(C) 3" through 8" sizes with large (1 1/4", 1 1/2", or 2") taps are 8" long with two 5/8" bolts.



HDPE Products are No Cancel, No Return Items.



The 305-H and 306-H are not to be used on HDPE pipe with an SDR greater than 26.

TO ORDER: Use pipe O.D. when ordering. Add tap size and thread type. Be specific when ordering. Indicate if for above ground application.

EXAMPLE: 305-H - 10.75 x 3/4" I.P.

HDPE