



STYLE 306

ALL STAINLESS STEEL SERVICE SADDLES

MATERIAL SPECIFICATIONS

SHELLS: Stainless steel per ASTM A240, type 304, passivated for corrosion resistance.

BOLTS: UNC rolled thread, 304 stainless steel.

NUTS: Stainless steel per ASTM A194, type 304.

WASHERS: Stainless steel type 304 and plastic lubricating washers.

GASKET: NBR per ASTM D2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

TAPPED OUTLET: Stainless steel per ASTM A240, type 304.



NSF61
CERTIFIED



MEETS
AWWA C800

306 DOUBLE BOLT (can be used with A/C pipe)						
NOM. PIPE SIZE	O.D. PIPE RANGE	TAP				APPROX. WEIGHT (lbs.)
		I.P.		C.C		
		1/2" - 1"	1 1/4" - 2"	3/4" - 1"	1 1/4" - 2"	
2"	2.13 2.38	\$146.24	N/A	\$146.24	N/A	2 #
		146.24	325.84 ³	146.24	N/A	2 #
2 1/2"	2.63 - 2.88	149.53	325.84 ³	149.53	N/A	2 #
3"	3.00 - 3.25 ¹	153.03	331.35	153.03	331.35	3 #
	3.25 - 3.50 ¹					
	3.50 - 3.75 ²					
	3.75 - 4.00 ²					
4"	4.00 - 4.30	175.47	339.79	175.47	339.79	4 #
	4.50 - 4.80					
	4.80 - 5.20					
5"	5.20 - 5.60	179.37	343.12	179.37	343.12	4 #
	5.60 - 6.00					
6"	6.00 - 6.40	250.93	353.13	250.93	353.13	4 #
	6.50 - 6.90					
	6.90 - 7.30					
8"	8.00 - 8.40	254.63	368.10	254.63	368.10	6 #
	8.63 - 9.05					
	9.05 - 9.45					
10"	10.00 - 10.40	310.22	388.16	310.22	388.16	8 1/2 #
	10.70 - 11.10					
	11.10 - 11.50					
12"	12.00 - 12.40	317.32	409.94	317.32	409.94	9 #
	12.75 - 13.20					
	13.20 - 13.60					

¹ Not available with 2" Tap.

² 2" CC Not Available.

³ Only available with 1 1/4" IP Tap.

For easiest installation, choose the saddle with your pipe O.D. closest to the bottom of the range. Other O.D.s available P.O.A.

306 LENGTH & BOLT SIZE	
(A)	2" through 5" nominal sizes with small (3/4" or 1") taps are 6" long with two 1/2" bolts.
(B)	3" through 5" sizes with large (1 1/4", 1 1/2", or 2") taps are 8" long with two 5/8" bolts.
(C)	6" through 12" sizes with small (3/4" or 1") taps are 6" long with two 5/8" bolts.
(D)	6" through 12" sizes with large (1 1/4", 1 1/2", or 2") taps are 8" long with two 5/8" bolts.

TO ORDER: Use upper range when ordering. Add tap size. Be specific when ordering.

Tapped outlet products are NO CANCEL/NO RETURN items.

EXAMPLE: 306 - 4.80 x 3/4" I.P.