

STYLE 517 BELL JOINT LEAK CLAMPS



MATERIAL SPECIFICATIONS

BELL AND SPIGOT RING: Ductile iron per ASTM A 536, Grade 65-45-12.

GASKET: SBR per ASTM D 2000 MBA 710, compounded for water and sewer service.

BOLTS: 1/2", mild steel all thread rod, zinc plated.

NUTS: Zinc plated, mild steel

USE: Romac's 517 Bell Joint Leak Clamps provide a fast, economical means of repairing or preventing leaks on Iron Pipe Size (IPS) PVC, and SDR35 Sewer Pipe.



NSF61 certified upon request.

Certified to
NSF/ANSI 61 & 372



8" BELL JOINT LEAK CLAMP
DUCTILE IRON POURED IN U.S.A.

| NOMINAL PIPE SIZE | O.D. SIZES (inches) | CATALOG NUMBER | BOLTS | | APPROX. WEIGHT (lbs.) | LIST PRICE |
|-------------------------|------------------------|-------------------|--------|---------------|--------------------------|------------|
| | | | NUMBER | DIA. x LENGTH | | |
| 4" | 4.22 | 517 - 4.22 | 4 | 1/2" x 12" | 13 # | \$262.11 |
| | 4.50 | 517 - 4.50 | 4 | 1/2" x 12" | 13 # | 262.11 |
| 6" | 6.28 | 517 - 6.28 | 4 | 1/2" x 12" | 15 # | 288.66 |
| | 6.63 | 517 - 6.63 | 4 | 1/2" x 12" | 15 # | 288.66 |
| 8" | 8.40 | 517 - 8.40 | 4 | 1/2" x 14" | 20 # | 399.38 |
| | 8.63 | 517 - 8.63 | 4 | 1/2" x 14" | 20 # | 399.38 |
| 10" | 10.50 | 517 - 10.50 | 6 | 1/2" x 14" | 28 # | 500.62 |
| | 10.75 | 517 - 10.75 | 6 | 1/2" x 14" | 28 # | 500.62 |
| 10" SDR 21 & thicker | 10.75 ¹ | 517 - 10.75 - 2 | 6 | 1/2" x 14" | 28 # | 500.62 |
| 12" | 12.50 | 517 - 12.50 | 6 | 1/2" x 14" | 31 # | 542.99 |
| | 12.75 | 517 - 12.75 | 6 | 1/2" x 14" | 31 # | 542.99 |
| 12" SDR 21 & thicker | 12.75 ¹ | 517 - 12.75 - 2 | 6 | 1/2" x 18" | 31 # | 542.99 |

¹ NBR gaskets are standard. For Class 200 (SDR21) or thicker wall pipe, longer bolts may be required.

NOTE: BJLC can be provided with double gasket and spigot halves for repairs on in-line couplings. Please provide coupling O.D. and length. All prices on application.



TO ORDER: Specify catalog number. Please provide bell OD and length.