



ARMOR LINK™ STAINLESS STEEL COUPLING

MATERIAL SPECIFICATIONS

SHELL AND ARMORS: 304 Stainless Steel, other materials available upon request.

GASKET: Ethylene Propylene Diene Monomer (EPDM) compounded for water and sewer service. Other compounds available on request.

BOLTS AND NUTS: 304 stainless steel, metric socket head cap screws. Other materials available upon request.

USE: For connection of pipe ends.

COMPATIBLE PIPE MATERIALS: Steel, Cast Iron, Ductile Iron, Asbestos Cement, Concrete, PVC & HDPE (PE 4710 & PE 3408).



Sizes 6 inch nominal and larger are NSF61 Certified.



A 48 INCH ARMOR LINK™ CONNECTING TO A VALVE.

- ALL STAINLESS STEEL.
- FAST STAB-FIT INSTALLATION.
- COMPATIBLE WITH STEEL, DI, HDPE, PVC, A/C AND CONCRETE PIPE.
- ACCOMODATES ANGULAR DEFLECTION AND MISALIGNED PIPES.



For Metric Hex Bit Sockets, see page 10-10

COUPLINGS

NOM. PIPE SIZE	O.D. (inches)	RANGE (inches)	CATALOG NUMBER	NOM. LENGTH	ALLOWABLE DEFLECTION	MAX OD DIFF.	WORKING PRESSURE †	HEX BIT SIZE	LIST PRICE	APPROX. WT. (lbs)
4"	4.50	4.41 - 4.61	ALINK-4.50	4"	2°	0.10	435	6mm	\$514.95	3.1
	4.80	4.76 - 4.84	ALINK-4.80	4"	2°	0.10	290	6mm	\$514.95	3.3
6"	6.63	6.54 - 6.73	ALINK-6.63	8"	2°	0.10	330	10mm	\$888.71	11.6
	6.90	6.77 - 7.01	ALINK-6.90	8"	2°	0.10	330	10mm	\$888.71	11.6
8"	8.63	8.54 - 8.78	ALINK-8.63	8"	2°	0.10	260	10mm	\$930.23	13.1
	9.05	8.82 - 9.06	ALINK-9.05	8"	2°	0.10	260	10mm	\$951.00	13.1
10"	10.75	10.63 - 10.87	ALINK-10.75	8"	2°	0.10	215	10mm	\$1,075.58	14.7
	11.10	10.94 - 11.18	ALINK-11.10	8"	2°	0.10	215	10mm	\$1,200.16	14.7
12"	12.75	12.60 - 12.83	ALINK-12.75	8"	2°	0.10	230	10mm	\$1,262.45	21.0
	13.20	13.15 - 13.39	ALINK-13.20	8"	2°	0.10	230	10mm	\$1,656.96	21.0
16"	17.40	17.32 - 17.56	ALINK-17.40	8"	2°	0.10	230	10mm	\$2,279.88	25.2
24"	25.80	25.59 - 25.91	ALINK-25.80	8"	2°	0.12	230	14mm	\$5,103.79	53.6

† Not to exceed pipe pressure rating. Imported.

Other sizes, lengths and tapped outlets available upon request.

For other compatible pipe materials, steam or air supply pipeline applications, contact Romac Engineering, 1.800.426.9341.



ARMOR LINK™ does not provide protection against possible pullout of pipe ends in unrestrained conditions. Pipe stiffeners are required on HDPE pipe.

TO ORDER: Specify catalog number.