

# STYLE CL2 (TWO SECTION) WIDER RANGE .80" w/ REMOVABLE LUGS



## MATERIAL SPECIFICATIONS

**SHELLS:** Stainless steel per ASTM A240, type 304.

**LUGS:** Ductile iron per ASTM A536, Grade 65-45-12. Boat-nose fingers designed for ease of installation. Lugs are removable. E-Coat epoxy coated for improved corrosion resistance.

**BOLTS AND NUTS:** Trackhead, 5/8" UNC rolled thread, high strength, low alloy, corrosion-resistant steel per AWWA C111. Coated to prevent galling. Stainless steel nuts and bolts available on request.

**GASKETS:** SBR per ASTM D2000 MAA 610, compounded for water and sewer service. Other compounds available on request.



CL2-9.39 x 12" REPAIR CLAMP

NSF61 certified upon request.

MEETS  
AWWA C230

NOM. PIPE SIZE	O.D. RANGE (inches)	CATALOG NUMBER	LENGTH / WEIGHT						
			7½"	10"	12"	15"	20"	25"	30"
4"	4.47 - 5.27	CL2 - 5.27 x length	\$310.67 21#	\$410.62 28#	\$484.76 34#	\$617.76 41#	\$922.39 55#	N/A	N/A
	4.77 - 5.57	CL2 - 5.57 x length							
	5.20 - 6.00	CL2 - 6.00 x length <sup>1</sup>							
6"	6.57 - 7.37	CL2 - 7.37 x length	360.37 22#	463.30 29#	540.66 37#	720.76 44#	961.02 58#	1,199.23 73#	1,473.19 88#
	6.84 - 7.64	CL2 - 7.64 x length							
	7.20 - 8.00	CL2 - 8.00 x length <sup>1</sup>							
8"	8.59 - 9.39	CL2 - 9.39 x length	407.58 23#	514.82 31#	600.65 39#	819.46 46#	1,063.94 62#	1,353.63 77#	1,643.12 93#
	8.99 - 9.79	CL2 - 9.79 x length							
	9.20 - 10.00	CL2-10.00 x length <sup>1</sup>							
10"	10.70 - 11.50	CL2-11.50 x length	427.52 24#	686.43 33#	949.78 41#	1,033.92 49#	1,372.88 65#	1,716.17 80#	2,059.32 98#
	11.04 - 11.84	CL2-11.84 x length							
	11.40 - 12.20	CL2-12.20 x length							
12"	12.70 - 13.50	CL2-13.50 x length	547.87 26#	763.60 34#	1,078.29 43#	1,132.58 52#	1,514.45 69#	1,889.97 86#	2,265.23 103#
	13.15 - 13.95	CL2-13.95 x length							
	13.50 - 14.30	CL2-14.30 x length							
14"	15.00 - 15.80	CL2-15.80 x length	801.23 28#	1,278.54 36#	1,370.39 45#	1,840.51 54#	2,488.31 72#	3,127.77 90#	3,766.83 108#
	15.95 - 16.75	CL2-16.75 x length							
	Add on for 304 stainless steel bolts & nuts								

<sup>1</sup> Recommended for use on CL200 ACRB.

**FOR TAPPED CL2 SEE PAGE 2-14.**

NUMBER OF BOLTS PER CLAMP LENGTH							
O.D. RANGE	7½"	10"	12"	15"	20"	25"	30"
All Ranges	6	8	10	12	16	20	24

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

**TO ORDER:** Specify catalog number x length of clamp desired.

**EXAMPLE:** For a two-section clamp for pipe with an O.D. between 8.59 and 9.39 and clamp length of 12" order **CL2 - 9.39 x 12"**

REPAIR CLAMPS