

STYLE CL2 (TWO SECTION) WIDER RANGE .80" w/ REMOVABLE LUGS



MATERIAL SPECIFICATIONS

SHELLS: Stainless steel per ASTM A 240, type 304.

LUGS: Ductile iron per ASTM A 536, Grade 65-45-12. Boat-nose fingers designed for ease of installation. Lugs are removable. E-Coat epoxy coated for improved corrosion resistance.

BOLTS AND NUTS: Trackhead, 5/8" UNC rolled thread, high strength, low alloy, corrosion-resistant steel per AWWA 111. Stainless steel nuts and bolts available on request.

GASKETS: SBR per ASTM D 2000 MAA 610, compounded for water and sewer service. Other compounds available on request.



CL2-9.39 X 12" REPAIR CLAMP



NSF61 certified upon request.

MEETS
AWWA C230

Certified to NSF/ANSI 61 & 372

NOM. PIPE SIZE	O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT						
			7½"	10"	12"	15"	20"	25"	30"
4"	4.47 - 5.27	CL2 - 5.27 x length	\$186.59 21#	\$246.62 28#	\$291.15 34#	\$371.03 41#	\$553.99 55#	N/A	N/A
	4.77 - 5.57	CL2 - 5.57 x length							
	5.20 - 6.00	CL2 - 6.00 x length ¹							
6"	6.57 - 7.37	CL2 - 7.37 x length	216.44 22#	278.26 29#	324.72 37#	432.89 44#	577.19 58#	720.26 73#	863.18 88#
	6.84 - 7.64	CL2 - 7.64 x length							
	7.20 - 8.00	CL2 - 8.00 x length ¹							
8"	8.59 - 9.39	CL2 - 9.39 x length	244.79 23#	309.20 31#	360.75 39#	492.17 46#	639.00 62#	812.99 77#	986.86 93#
	8.99 - 9.79	CL2 - 9.79 x length							
	9.20 - 10.00	CL2-10.00 x length ¹							
10"	10.70 - 11.50	CL2-11.50 x length	256.77 24#	412.27 33#	570.44 41#	620.97 49#	824.55 65#	1,030.73 80#	1,236.83 98#
	11.04 - 11.84	CL2-11.84 x length							
	11.40 - 12.20	CL2-12.20 x length							
12"	12.70 - 13.50	CL2-13.50 x length	329.05 26#	458.62 34#	647.62 43#	680.23 52#	909.58 69#	1,135.12 86#	1,360.50 103#
	13.15 - 13.95	CL2-13.95 x length							
	13.50 - 14.30	CL2-14.30 x length							
	13.71 - 14.51	CL2-14.51 x length							
14"	15.00 - 15.80	CL2-15.80 x length	481.22 28#	767.89 36#	823.06 45#	1,105.41 54#	1,494.48 72#	1,878.54 90#	2,262.36 108#
	15.95 - 16.75	CL2-16.75 x length							
Add on for 304 stainless steel bolts & nuts			65.00	91.27	116.89	136.98	182.64	228.20	273.86

¹ Recommended for use on CL200 ACRB.

FOR TAPPED CL2 SEE PAGE 2-14.

NUMBER OF BOLTS PER CLAMP LENGTH

OD RANGE	7½"	10"	12"	15"	20"	25"	30"
All Ranges	6	8	10	12	16	20	24

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

TO ORDER: Specify catalog number x length of clamp desired.

EXAMPLE: For a two-section clamp for pipe with an O.D. between 8.59 and 9.39 and clamp length of 12" order **CL2 - 9.39 x 12"**