



# STYLE CL3 (THREE SECTION) WIDEST RANGE 1.20" w/ REMOVABLE LUGS

## MATERIAL SPECIFICATIONS

**SHELLS:** Stainless steel per ASTM A 240, type 304.

**LUGS:** Ductile iron per ASTM A 536, Grade 65-45-12. Boat-nose fingers designed for ease of installation. Lugs are removable. E-Coat epoxy coated for improved corrosion resistance.

**BOLTS AND NUTS:** Trackhead, 5/8" UNC rolled thread, high strength, low alloy, corrosion-resistant steel per AWWA 111. Stainless steel nuts and bolts available on request.

**GASKETS:** SBR per ASTM D 2000 MAA 610, compounded for water and sewer service. Other compounds available on request.



CL3-18.30 X 12" REPAIR CLAMP



NSF61 certified upon request.

MEETS  
AWWA C230

O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT						
		7½"	10"	12"	15"	20"	25"	30"
11.04 - 12.24 12.40 - 13.60	CL3-12.24 x length CL3-13.60 x length	\$377.88 30#	\$442.12 39#	\$550.69 48#	\$659.20 58#	\$873.61 77#	\$1,096.03 96#	\$1,318.50 115#
13.14 - 14.34 13.45 - 14.65	CL3-14.34 x length CL3-14.65 x length	433.02 34#	479.69 45#	596.24 56#	712.83 68#	948.62 90#	1,184.51 112#	1,420.29 130#
15.30 - 16.50 17.10 - 18.30	CL3-16.50 x length CL3-18.30 x length	629.24 36#	861.65 48#	887.79 60#	1,053.10 72#	1,425.95 96#	1,890.28 120#	2,354.53 144#
18.00 - 19.20 19.50 - 20.70	CL3-19.20 x length CL3-20.70 x length	645.79 37#	871.08 50#	937.68 62#	1,135.56 75#	1,537.65 99#	2,015.38 124#	2,492.10 149#
21.60 - 22.80	CL3-22.80 x length	714.85 38#	955.46 51#	1037.47 64#	1,175.53 77#	1,591.71 102#	2,146.60 128#	2,701.17 153#
23.25 - 24.45	CL3-24.45 x length	948.89 40#	1,237.54 52#	1,296.30 66#	2,045.36 79#	2,770.92 105#	3,481.39 132#	4,191.82 158#
25.80 - 27.00	CL3-27.00 x length	1,182.84 41#	1,519.41 54#	1,555.05 68#	2,186.70 81#	2,966.48 108#	3,727.79 136#	4,485.85 162#
Add on for 304 stainless steel bolts & nuts		97.49	136.91	175.33	205.46	273.96	342.30	410.79

FOR TAPPED CL3 SEE PAGE 2-14.

### NUMBER OF BOLTS PER CLAMP LENGTH

OD RANGE	7½"	10"	12"	15"	20"	25"	30"
All Ranges	9	12	15	18	24	30	36

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

**TO ORDER:** Specify catalog number x length of clamp desired.

**EXAMPLE:** For a 3-section clamp for pipe with an O.D. between 17.10 and 18.30 and clamp length of 12" order **CL3 - 18.30 x 12"**