TAPS FOR REPAIR CLAMPS SS1-H, SS2-H AND SS3-H

MADE IN U.S.A. HDPE FOR HIGH DENSITY POLYETHYLENE PIPE

AVAILABLE IN ALL STYLES

The same design, construction, and installation features as Styles SS1-H, SS2-H and SS3-H. Tapped outlet is stainless steel per ASTM A240, type 304, permanently "fused" by GTAW welding, and fully passivated [1].





6" SS1-H - 6.63 × 12 × ¾"
IP TAPPED REPAIR CLAMP



For above-ground HDPE applications, contact Romac's Engineering Department at 1-800-426-9341.

Products and prices listed below are standard Romac sizes. For information on other sizes, contact Romac's Engineering Department.

For important technical information on HDPE pipe, see Page 9-1 & Page 9-2.

ADD ON LIST PRICES FOR TAPPED CLAMPS

TAP SIZE	TYPE OF THREAD	MINIMUM PIPE O.D.	MINIMUM LENGTH	ADD ON LIST PRICE
¾"	Iron Pipe or AWWA Taper (CC)	2.38"	8"	$105.14
1"	Iron Pipe or AWWA Taper (CC)	2.38"	8"	105.14
1¼"	Iron Pipe or AWWA Taper (CC)	3.50"	12"	164.80
1½"	Iron Pipe or AWWA Taper (CC)	3.50"	12"	164.80
2"	Iron Pipe	3.50"	12"	164.80
2"	AWWA Taper (CC)	4.85"	12"	201.78
2½"[3]	Iron Pipe only (MIP, FIP)	6.63" [4]	12"	466.05
3"[3]	Iron Pipe only (MIP, FIP) SS2, SS3 only	8.63" [4]	12"	466.05

[1] Passivated: Chemically treated after welding to produce a highly corrosion-resistant coating.
[2] Requires SS2-H or SS3-H
[3] MIP only

⚠ HDPE Products are No Cancel, No Return Items.

⚠ The SS1-H, SS2-H and SS3-H are not to be used on HDPE pipe with an SDR greater than 26.

TO ORDER:

1. Select size, length, and style of clamp.
2. Select size and type of tapped thread desired from the table below.
3. Add list price for tap to the list price of clamp selected from separate price sheet.
4. Indicate if for above ground application.

EXAMPLE: For a one-section clamp for pipe with an O.D. of 6.63, with length of 12" and a 3/4" iron pipe tap size, order **SS1-H-6.63 x 12 x 3/4" IP**

Manufactured with Domestic and Import material. For Domestic requirements please contact our Quotations Department.
JANUARY 10, 2022 • UPDATED JULY 9, 2026