

# **T-BOLTS & N**

# MATERIAL SPECIFICATIONS

T-BOLT: High Strength, Low-Alloy / Corrosion Resistant Steel, (Cor-Ten TM), (Mayari- R TM). Meets or exceeds ASTM A588, Grade A, AWWA C111 composition specifications. The material specifications of ASTM A588 meets or exceeds ASTM A307 Grade A.

NUT: High Strength, Low-Alloy / Corrosion Resistant Steel, (Cor-Ten ™), (Mayari- R ™). Meets or exceeds ASTM A563 Grade, C3, AWWA C111 composition specifications. The material specifications of ASTM A563 Grade C3 meets or exceeds ASTM A563 Grade A.

COATING: Xylan 1424 polytetrafluoroethylene (PTFE) a dry-film lubricant (VOC compliant), resin bonded, PTFE based coating formulated for use on fasteners to prevent corrosion and facilitate make up torque.

BASE COAT: Zinc plating.



## ROMAC R-BLUE ADVANTAGES

- LOW FRICTION
  - Reduces make up torque as much as 70%.
- EXCEPTIONAL CORROSION RESISTANCE Xylan 1424 with Zinc Plating base coat survives salt fog testing (ASTM B117) for up to 2,500 hours.
- RESISTANT TO ABRASION, WEAR & CHIPPING. Achieves a 5A rating for adhesion per ASTM D3359.



#### XYLAN 1424

Formulated specifically for waterworks applications, the Xylan 1424 top coat simultaneously provides lubricity and superior corrosion protection.

#### ZINC PLATING

Zinc plating base coat provides an additional layer of protection that outperforms other surface preparations.

### **ROMAC R-BLUE T-BOLTS & NUTS**

1		CATALOG	LIST PRICE			ACCESSORY WEIGHT EACH (lbs.)		
	BOLT SIZE	NUMBER	EACH	4 PACK	6 PACK	EACH	4 PACK	6 PACK
	5/8" x 3"	3" - R-BLUE	\$8.03	NA	NA	0.5	NA	NA
ı	3/4" x 3 1/2"	3.5" - R-BLUE	9.31	NA	NA	0.75	NA	NA
	3/4" x 4"	4" - R-BLUE	NA	\$39.54	\$59.32	0.85	3.40	5.10
ı	3/4" x 4 1/2"	4.5" - R-BLUE	NA	43.11	64.67	0.90	3.60	5.40
	3/4" x 5"	5" - R-BLUE	NA	49.43	NA	0.95	3.80	NA

**TO ORDER:** Specify catalog number and bolt / pack quantity.