



STYLE SS2 (TWO SECTION) WIDER RANGE .80"

MATERIAL SPECIFICATIONS

- SHELLS AND LUGS:** Stainless steel per ASTM A 240, type 304.
- BOLTS:** UNC rolled thread, stainless steel per ASTM A 193, type 304.
- NUTS:** Stainless steel per ASTM A 194, type 304.
- WASHERS:** Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.
- GASKETS:** SBR per ASTM D 2000 MAA 610. Compounded for water and sewer service. Other compounds available on request.



SS2-7.64 X 10" REPAIR CLAMP



NSF61 certified upon request.

MEETS
AWWA C230

REPAIR CLAMPS

NOM. PIPE SIZE	O.D. SIZE RANGE	CATALOG NUMBER	LENGTH / WEIGHT						
			8"	10"	12"	16"	20"	24"	30"
4"	4.47 - 5.27 4.77 - 5.57 5.20 - 6.00	SS2 - 5.27 x length SS2 - 5.57 x length SS2 - 6.00 x length ¹	\$241.19 9#	\$316.79 12#	\$375.14 13#	\$448.49 17#	\$600.60 25#	\$768.14 30#	N/A
6"	6.57 - 7.37 6.84 - 7.64 7.20 - 8.00	SS2 - 7.37 x length SS2 - 7.64 x length SS2 - 8.00 x length ¹	277.26 11#	356.70 15#	406.29 17#	524.57 22#	716.04 28#	941.44 34#	1013.47 43#
8"	8.59 - 9.39 8.99 - 9.79 9.20 - 10.00	SS2 - 9.39 x length SS2 - 9.79 x length SS2-10.00 x length ¹	317.35 12#	396.04 17#	461.58 19#	600.60 24#	813.07 30#	1,075.28 36#	1,143.12 47#
10"	10.70 - 11.50 11.04 - 11.84 11.40 - 12.20	SS2-11.50 x length SS2-11.84 x length SS2-12.20 x length	320.84 15#	519.32 18#	712.79 23#	747.47 32#	996.65 41#	1,324.96 47#	1,493.40 59#
12"	12.70 - 13.50 13.15 - 13.95 13.50 - 14.30 13.71 - 14.51	SS2-13.50 x length SS2-13.95 x length SS2-14.30 x length SS2-14.51 x length	411.20 16#	595.37 19#	809.26 25#	855.02 33#	1,154.02 41#	1,471.91 50#	1,681.79 61#
14"	15.00 - 15.80 15.95 - 16.75	SS2-15.80 x length SS2-16.75 x length	589.53 18#	796.11 21#	1028.49 27#	1,146.40 33#	1,552.31 43#	1,836.35 50#	1,933.44 64#

¹ Recommended for use on CL200 ACRB

NUMBER OF BOLTS PER CLAMP LENGTH							
OD RANGE	8"	10"	12"	16"	20"	24"	30"
4.47 - 9.99	4	6	6	8	10	12	16
10.00 - 16.75	6	6	8	10	14	16	20

FOR TAPPED SS2 SEE PAGE 2-14.
FOR SEWER O.D.S SEE PAGE 7-8.

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

TO ORDER: Specify catalog number x length of clamp desired.

EXAMPLE: For a two-section clamp for pipe with an O.D. between 6.84 and 7.64 and clamp length of 10", order **SS2 - 7.64 x 10"**