

STYLE SS3 (THREE SECTION)

WIDEST RANGE 1.20"



MATERIAL SPECIFICATIONS

SHELLS AND LUGS: Stainless steel per ASTM A 240, type 304.

BOLTS: UNC rolled thread, stainless steel per ASTM A 193, type 304.

NUTS: Stainless steel per ASTM A 194, type 304.

WASHERS: Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.

GASKETS: SBR per ASTM D 2000 MAA 610. Compounded for water and sewer service. Other compounds available on request.



SS3-14.65 X 12" REPAIR CLAMP



NSF61 certified upon request.

**MEETS
AWWA C230**

Certified to
NSF/ANSI 61 & 372

| O.D. SIZE RANGE | CATALOG NUMBER | LENGTH / WEIGHT | | | | | | | |
|----------------------------|------------------------------------------|-----------------|-----------------|-----------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| | | 8" | 10" | 12" | 16" | 20" | 24" | 30" | 36" |
| 11.04-12.24 12.40-13.60 | SS3-12.24 x length SS3-13.60 x length | \$490.73 22# | \$657.06 27# | \$824.62 31# | \$1,111.93 41# | \$1,597.67 53# | \$1,624.60 61# | \$1,864.75 80# | \$2,709.78 94# |
| 13.14-14.34 13.45-14.65 | SS3-14.34 x length SS3-14.65 x length | 562.24 24# | 729.99 29# | 936.16 33# | 1,187.47 43# | 1,643.57 56# | 1,802.97 65# | 2,099.81 85# | 2,831.03 99# |
| 15.30-16.50 17.10-18.30 | SS3-16.50 x length SS3-18.30 x length | 742.69 25# | 1,118.84 30# | 1,152.78 35# | 1,495.14 45# | 1,986.34 59# | 2,078.91 72# | 3,057.45 89# | 3,481.41 103# |
| 18.00-19.20 19.50-20.70 | SS3-19.20 x length SS3-20.70 x length | 838.54 26# | 1,145.38 32# | 1,217.57 36# | 1,524.78 49# | 2,067.25 63# | 2,555.88 76# | 3,237.14 95# | 3,592.30 112# |
| 21.60-22.80 | SS3-22.80 x length | 928.22 30# | 1,240.68 35# | 1,347.15 40# | 1,727.26 53# | 2,293.98 67# | 2,613.65 80# | 3,507.69 102# | 4,021.45 120# |
| 23.25-24.45 | SS3-24.45 x length | 1,232.11 33# | 1,367.56 38# | 1,519.62 43# | 2,213.16 56# | 2,982.30 71# | 3,420.21 84# | 4,318.50 109# | 5,195.48 129# |
| 25.80-27.00 | SS3-27.00 x length | 1,535.82 35# | 1,626.87 40# | 1,697.03 45# | 2,698.83 60# | 3,670.35 75# | 4,226.32 88# | 4,777.20 115# | 6,369.55 135# |

NUMBER OF BOLTS PER CLAMP LENGTH

| OD RANGE | 8" | 10" | 12" | 16" | 20" | 24" | 30" | 36" |
|------------|----|-----|-----|-----|-----|-----|-----|-----|
| All Ranges | 9 | 9 | 12 | 15 | 21 | 24 | 30 | 36 |

FOR TAPPED SS3 SEE PAGE 2-14.

FOR SEWER O.D.S SEE PAGE 7-8.

For higher working pressures, clamp length should equal or exceed diameter of pipe. Some sizes and lengths not listed are available on request. Clamps are not to be used for joining plain end pipe.

TO ORDER: Specify catalog number x length of clamp desired.

EXAMPLE: For a 3-section clamp for pipe with an O.D. between 13.45 and 14.65 and clamp length of 12", order **SS3 - 14.65 x 12"**