
				•
NOMINAL SIZE (IN)	PIPE OD (IN)	RADIUS (IN)	LENGTH (IN)	"N" # OF WASHERS
4	4.50	2.25	7.06	2
4	4.80	2.40	7.20	2
6	6.63	3.32	9.04	2
	6.90	3.45	9.18	2
8	8.63	4.32	10.77	3
0	9.05	4.53	11.20	3
10	10.75	5.38	13.10	3
10	11.10	5.55	13.21	3
12	12.75	6.38	15.09	4
12	13.20	6.60	15.25	4

			CAD-021	168
		REVISIONS	•	
RE	V.	DESCRIPTION	DATE	EDITOR
R3 –	Α	UPDATED ALL LENGTHS.	6/20/22	KKT
IN3	В	REMOVED NYLON THICKNESS.	0/20/22	IXIX I
		LENGTH	- 4.00	- 1



NOTES:

- 1. CASTING BODY: DUCTILE IRON PER ASTM A536 65-45-12.
- 2. STRAP, STUD, & NUT: TYPE 304 STAINLESS STEEL.
- 3. STUD & NUT: 5/8-11 UNC.
- 4. WASHERS:
 - 1 EACH OF: 304SS & ACETAL PLASTIC.
 - "N" AMOUNT OF SPRING WASHERS.
- 5. OUTLET: UP TO 2.5" "IP" (NPT) OR 2" "CC" (PER AWWA C800) TAP SIZES.
- 6. GASKET: NBR PER ASTM D2000 MBC 610. EPDM AVAILABLE UPON REQUEST.
- 7. WELDING: GMAW. CHEMICALLY CLEANED AND PASSIVATED.
- 8. COATING:
 - CASTING: NYLON COATING B
 - NUTS: BLACK EPOXY E-COAT
- 9. FOR USE ON HDPE PIPE WITH MINIMUM WALL THICKNESS OF SDR 26.

PROPRIETARY NOTICE	UNLESS OTHERWISE SPECIFIED	SIGNATURES	DATE		ROMAC INDUSTRIES INC.				
THIS DRAWING CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION AND IS THE PROPERTY OF ROMAC IND., INC. IT IS TO BE USED ONLY FOR THE PURPOSE FOR WHICH IT WAS SUBMITTED AND SHALL NOT HAVE ITS INFORMATION DISCLOSED OR REPRODUCED IN WHOLE OR IN PART FOR ANY PURPOSE WITHOUT PRIOR WRITTEN PERMISSION OF ROMAC IND., INC.	DIMENSIONS ARE IN INCHESDRAWING NOT TO SCALE.	DRAWN Kevin Tam	6/20/2022		DI SADDLES 202NH, 4" - 12"				
		APPROVED Tanja Parviainen	6/21/2022		DWG. NO. CAD-021168	SIZE A	REV. NO.	SCALE NTS	SHEET 1 OF 1
MODEL NAME: SERVICE SADDLE, ASSEM, DI, 202, 07:60 IN CONFIGURATION NAME: HDPE MODEL CAD #: CAD-050490		THIRD ANGLE PROJECTION	\bigoplus	LEGACY DRAWING #: N/A DRAWING FILE NAME: SERVICE SADDLE, ASSEM, DI, 202, HDPE, 4 - 12 IN		AUTHOR: Kev	in Tam		