

# ARMOR-LINK™

## FLEXIBLE COUPLING FOR PIPE CONNECTION

### SUBMITTAL INFORMATION



Sizes 6 inch nominal and larger are NSF61 Compliant.

### MATERIALS

#### SHELL

304L Stainless Steel (other materials available upon request).

#### SIDEBARS

304 Stainless Steel (other materials available upon request).

#### BOLTS

304 Stainless Steel. Metric socket head cap screw, coated to prevent galling.

#### ARMORS

304 Stainless Steel (other materials available upon request).

#### GASKET

Ethylene Propylene Diene Monomer (EPDM) compound for water and sewer service. Temperature rating is -4° to 212°F. NBR and Silicone available upon request.

#### WELDS

GMAW and GTAW welds. 316L Stainless Steel filler wire used as appropriate. All welds fully passivated for enhanced corrosion resistance.

### PROPERTIES

NOM. PIPE SIZE	ALLOWABLE DEFLECTION	WORKING PRESSURE	APPROXIMATE WEIGHT (LBS)
4"	2°	440	3.1
	2°	290	3.3
6"	2°	340	11.6
	2°	340	11.6
8"	2°	260	13.1
	2°	260	13.1
10"	2°	220	14.7
	2°	220	14.7
12"	2°	230	21.0
	2°	230	21.0
16"	2°	230	25.2
24"	2°	230	53.6

Test pressure is 1.5 times that of working pressure.

### STANDARDS

Complies with AWWA C227 Bolted, Split Sleeve Couplings for Plain End Pipe.

### SIZES & RANGES

See catalog.

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.