

# SL1 & SL2 PIPE REPAIR CLAMP WITH REMOVEABLE BOLTS

## SUBMITTAL INFORMATION



## MATERIALS

### SHELL

304 Stainless Steel 22 or 20 gauge depending on size.

### SIDEBARS

Heavy gauge 304 Stainless Steel, GTAW welded to form permanent fusion with shell.

### LUGS

3/16" 304 Stainless Steel, fused to sidebars by GMAW welding.

### BOLTS

5/8"-11 UNC thread track head, type 304 stainless steel per ASTM A 193.

### NUTS

5/8" heavy hex, type 304 Stainless Steel per ASTM A 194. Nuts coated to prevent galling.

### ARMORS

Heavy gauge 304 Stainless Steel, bonded to gasket to bridge gap at lug area.

### GASKETS

Virgin SBR rubber compounded for water and sewer service in accordance with ASTM D 2000 MAA 610. Other compounds available for petroleum or high temperature service, or other special applications.

## WELDS

GMAW and GTAW welds. 308L Stainless Steel filler wire used as appropriate. All welds fully passivated for enhanced corrosion resistance.

## STANDARD

Complies with ANSI/AWWA Standard C230 Stainless-Steel Full-encirclement Repair and Service Connection Clamps 2" – 12".

## SIZES & RANGES

See catalog.