ECF400 EQUIPMENT CONNECTION FITTING
14" – 72" AWWA CLASS "D" AND "E"

SUBMITTAL INFORMATION

NSF61/372 Certified.

USE

Provides offset, deflection and restraint if your system has misaligned flanges that need to be connected.

MATERIALS

FLANGES
AWWA Class D and E steel ring flanges per C207, compatible with ANSI Class 125 and 150 bolt circles.

SPOOL
ASTM A 36 steel, pipe stops are available on request.

END RINGS AND BODIES
ASTM A-36 steel.

GASKETS
Compounded for water and sewer service. Meeting the requirements of ASTM D 2000. Other compounds available on request.

BOLTS, NUTS AND SPHERICAL WASHERS
ASTM A588 HSLA bolt material. Stainless Steel, Types 304 or 316 is optional.

TIE RODS
High tensile steel per ASTM A193 grade B7. Stainless steel, type 304 or 316 is optional.

HARNESS LUGS
ASTM A36 steel, coated with fusion bonded epoxy.

COATINGS
All steel and ductile parts are coated with fusion bonded epoxy, NSF 61 certified.

PRESSURE

When properly installed properly the Romac style ECF400 14" – 72" are rated up to the maximum rating of the flange. AWWA Class D flanges are rated for 150 psi and AWWA Class E flanges are rated for 275.

SIZE

14" – 72" See catalog. Larger sizes available on request.

10/23/2025
Document # 20-8-0024

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.

ROMAC INDUSTRIES, INC.
www.romac.com
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201