

RFCA- PVC RESTRAINED FLANGE COUPLING ADAPTER FOR PVC PIPE 14 - 24 IN.

SUBMITTAL INFORMATION



NSF61/372 Certified upon request.

USE

The Restrained Flanged Coupling Adapter is used to connect plain end C905 PVC pipe to a standard ANSI class 125 and 150 bolt circle. It provides flexibility before and after installation. The RFCA replaces costly concrete thrust blocks, corrodible steel tie rods and clamps.

MATERIALS

GLAND AND FLANGE BODY

Ductile (nodular) iron, meeting or exceeding ASTM A 536, Grade 65-45-12.

GASKET

MJ Gasket per AWWA C111 is made from virgin Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D 2000 MBA 710. Flange gasket is O ring style and is made of Nitrile Butadiene Rubber (NBR) in accordance with ASTM D 2000. Other compounds available for petroleum, chemical, or high temperature service.

RESTRAINING BOLT

7/8 – 9 roll thread, Ductile (nodular) iron, meeting or exceeding ASTM A 536.

RESTRAINING LUGS

Ductile (nodular) iron, meeting or exceeding ASTM A 536. Heat treated using a proprietary process.

LUG LOCATORS

Type 304 stainless steel.

GLAND BOLTS AND NUTS

High strength low alloy steel T-head bolt. National coarse rolled thread and heavy hex nut. Steel meets ASTM A 588 composition specifications. Stainless steel bolts and nuts available on request, this option will be provided as all thread rod and two nuts.

COATINGS

Shop coat applied to cast parts for corrosion protection in transit. Fusion bonded epoxy, RomaGrip Romabond polyester, available on request.

FLANGE

Compatible with ANSI Class 125 and 150 bolt circles.

STANDARD

Romac couplings meet the specifications set forth in the AWWA Standard C219 coupling spec.

12/3/2024

Document # 20-8-0021

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.

RFCA- PVC

RESTRAINED FLANGE COUPLING ADAPTER FOR PVC PIPE 14 - 24 IN.

SUBMITTAL INFORMATION

PIPE COMPATIBILITY AND TORQUE

PIPE MATERIAL	PIPE SIZE	WORKING PRESSURE	RECOMMENDED TORQUE FOR T-BOLTS	RECOMMENDED TORQUE FOR RESTRAINING BOLTS
PVC - D.I. Size (C905 Class 100, DR 41)	14"	80 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 100, DR 41)	16" - 24"	100 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 125, DR 32.5)	14" - 24"	125 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 165, DR 25)	14" - 24"	165 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 235, DR 18)	14" - 16"	235 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 235, DR 18)	18" - 20"	200 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 235, DR 18)	24"	165 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 305, DR 14)	14" - 16"	235 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 305, DR 14)	18" - 20"	200 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. Size (C905 Class 305, DR 14)	24"	165 PSI	75-90 ft-lbs.	TORQUE OFF HEADS
PVC - D.I. SIZE (C909)	NOT COMPATIBLE WITH RFCA-PVC			
PVC - "CLASS PIPE" (IPS SIZE)				
DUCTILE IRON				
STEEL				
ASBESTOS CEMENT				
FIBERGLASS				
HDPE				

*WORKING PRESSURES ARE DESIGNED WITH A 2:1 SAFETY FACTOR

DEFLECTION

Maximum joint deflection for 14" and 16" is 2.00 degrees and for 18" – 24" is 1.5 degrees.

SIZES & RANGES

See Catalog.

05/12/2020

Document # 20-8-0021

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.



www.romac.com
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201