

# 416 BJLC BELL JOINT LEAK CLAMP

## SUBMITTAL INFORMATION



NSF61/372 Certified upon request.

## USE

Provide a fast, economical means of repairing or preventing leaks in ductile iron and cast iron pipe bells.

## MATERIALS

### LEAK CLAMP

The bell ring and spigot ring are made from mild steel meeting or exceeding ASTM A 36.

### GASKETS

Compounded for water and sewer service. Meeting the requirements of ASTM D 2000. Other compounds available on request.

### BOLTS AND NUTS

High strength low alloy steel trackhead bolts or all-thread rod. National coarse rolled thread and heavy hex nuts. Steel meets AWWA C111. Type 304 and 316 Stainless Steel bolt material optional.

### COATINGS

Shop coat applied to BJLC parts for corrosion protection in transit. Fusion bonded epoxy, liquid epoxy and other coatings available on request.

## PRESSURE

When properly installed on a pipe that is within the correct outside diameter range, Romac Style 416 Bell Joint Leak Clamps can be used at working pressures up to 150 psi.

## SIZES & RANGES

12 inch and larger 416 BJLC are fabricated to fit all standard ductile iron pipe and bell dimensions. For other pipe materials please provide bell and pipe dimensions.

11/25/2024

Document # 30-8-0011

*This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.*