FJ-RESTRAINT FLEXIBLE BALL JOINT RESTRAINT
FITTING FLANGED ENDS 14" THROUGH 24"

SUBMITTAL INFORMATION

USE

The FJ-Restraint is a flexible ductile iron fitting, developed to accommodate pipeline forces that would otherwise result in damaged pipe or loss of service. The FJ-Restraint is designed to compensate for expansion, contraction, rotation, bending and settlement of your pipeline all at the same time, with one fitting. Designed for use in buried applications or above ground service.

MATERIALS

CASTINGS
The casing, ball and Sleeve are cast of ductile (nodular) iron, meeting or exceeding ASTM A 536, Grade 65-45-12.

FLANGE
Compatible with ANSI Class 125 and 150 bolt circles.

LOCK RING
Series 400 stainless steel. Limits expansion and contraction of FJ-Restraint up to maximum working pressure.

RING GASKETS
Ring gaskets are made of dual Ethylene Propylene Diene Methylene (EPDM) compounded for water and sewer service.

CASING COVERS
14 - 24 inch covers are Protective Polyethylene debris cover.

COATINGS
The entire fitting is lined and coated with fusion bonded epoxy, NSF61 Certified, applied in accordance with AWWA C213.

PROTECTIVE SLEEVE
Polyethylene sleeve, 8 mils thick per AWWA C105 to cover entire FJ-Restraint assembly after installation. Provided with flexible rubber bands to secure to pipe ends and FJ-Restraint.

PRESSURE

When properly installed the FJ-Restraint can be used at working pressures up to 350 psi.

SIZES & RANGE

See Catalog.

Document # 5-8-0015 14 - 24 inch 11/27/2024

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.

ROMAC INDUSTRIES, INC.
www.romac.com
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201