

# FJ-RESTRAINT FLEXIBLE BALL JOINT RESTRAINT FITTING FLANGED ENDS 3" THROUGH 12"

## SUBMITTAL INFORMATION



NSF61/372 Certified upon request.

## USE

The FJ-Restraint is a flexible ductile iron fitting, developed to accommodate pipeline forces that would otherwise result in damaged pipe or loss of service. The FJ-Restraint is designed to compensate for expansion, contraction, rotation, bending and settlement of your pipeline all at the same time, with one fitting. Designed for use in buried applications or above ground service.

## MATERIALS

### CASTINGS

The casing, ball and Sleeve are cast of ductile (nodular) iron, meeting or exceeding ASTM A 536, Grade 65-45-12.

### FLANGE

Compatible with ANSI Class 125 and 150 bolt circles.

### LOCK RING

Series 400 stainless steel. Limits expansion and contraction of FJ-Restraint up to maximum working pressure.

### RING GASKETS

Ring gaskets are made of dual Ethylene Propylene Diene Methylene (EPDM) compounded for water and sewer service.

### CASING COVERS

3 - 12 inch covers are made of Ethylene Propylene Diene Methylene, (EPDM).

### COATINGS

The entire fitting is lined and coated with fusion bonded epoxy, NSF61 Certified, applied in accordance with AWWA C213.

### PROTECTIVE SLEEVE

Polyethylene sleeve, 8 mils thick per AWWA C105 to cover entire FJ-Restraint assembly after installation. Provided with flexible rubber bands to secure to pipe ends and FJ-Restraint.

## PRESSURE

When properly installed the FJ-Restraint can be used at working pressures up to 350 psi.

## FM APPROVED

3 inch through 12 inch.

## SIZES & RANGE

See Catalog.

11/27/2024

Document # 5-8-0015 3 - 12 inch

*This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.*



www.romac.com  
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021  
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201