

EPDM "O" RING GASKETS ETHYLENE PROPYLENE DIENE MONOMER RUBBER

SUBMITTAL INFORMATION

USE

Ethylene Propylene Diene Monomer Rubber, commonly known as EPDM, is formulated for applications involving high temperatures and many harsh chemicals. For more information contact our factory.

Rubber Compounded Per ASTM D 2000 SAE

CHARACTERISTICS

| | |
|-------------------------|------------------|
| Temperature Range: | -40°F to +250°F |
| High Intermittent Range | 300°F |
| Weathering: | Excellent |
| Abrasion: | Good - Excellent |
| Compression Set: | Good - Excellent |
| Tearing: | Good - Excellent |
| Steam Service: | Excellent |

CHEMICAL RESISTANCE

| | |
|------------------|-----------------|
| HCO ₃ | Excellent |
| Fluorides | Excellent |
| Sodium Compounds | Excellent |
| Sulfuric Acid | Good |
| Hydrocarbons | Not recommended |

12/12/18

Document # 45-8-0042

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.



www.romac.com
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201