

FTS420T SERVICE SADDLE

SERVICE SADDLE WITH THREADED OUTLET

SUBMITTAL INFORMATION



MATERIALS

BODY

ASTM A 36 Steel Plate.

TAP

NPT or AWWA (CC), male or female threads.

BOLTS AND NUTS

High strength low alloy steel bolts and nuts. Steel meets AWWA Standard C111. Type 304 and 316 Stainless Steel bolt material optional.

GASKETS

Gaskets are made Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D 2000 3 BA715. Other compounds available for petroleum, chemicals, or high temperature service.

COATINGS

Shop coat applied to parts for corrosion protection in transit. Fusion bonded epoxy in accordance with AWWA C213 optional.

PRESSURE

250 psi 6 inch through 24 inch with up to 8 inch outlets. 200 psi for 28 inch nominal with up to 8 inch outlets. 150 psi 30 inch to 42 inch with up to 8 inch outlets. 100 psi larger than 42 inch with up to 8 inch outlets. Higher pressure ratings can be accommodated. Consult your representative.

STANDARD

The FTS420T service saddle meets the requirements of ANSI/AWWA C800, Underground Service Line Valves and Fittings.

SIZES & RANGES

See catalog, for larger sizes consult your representative.

1/17

Document # 30-8-0038

This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.



www.romac.com
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201