

# FTS420T SERVICE SADDLE

## SERVICE SADDLE WITH THREADED OUTLET

### SUBMITTAL INFORMATION



NSF61/372 Certified upon request.

### MATERIALS

#### BODY

ASTM A 36 Steel Plate.

#### TAP

NPT or AWWA (CC), male or female threads.

#### BOLTS AND NUTS

High strength low alloy steel bolts and nuts. Steel meets AWWA Standard C111. Type 304 and 316 Stainless Steel bolt material optional.

#### GASKETS

Gaskets are made Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D 2000 3 BA715. Other compounds available for petroleum, chemicals, or high temperature service.

#### COATINGS

Shop coat applied to parts for corrosion protection in transit. Fusion bonded epoxy in accordance with AWWA C213 optional.

### PRESSURE

6 - 24 INCH Nominal with up to 8 INCH outlet = 250 PSI

26 - 28 INCH Nominal with up to 8 INCH outlet = 200 PSI

30 - 42 INCH Nominal with up to 8 INCH outlet = 150 PSI

Larger than 42 INCH Nominal with up to 8 INCH outlet = 100 PSI

Higher pressure ratings can be accommodated, please consult your representative.

### STANDARD

Contact Romac Engineering for ANSI/AWWA C800 Spec and Approval Chart.

### SIZES & RANGES

See catalog, for larger sizes consult your representative.

11/27/2024

Document # 30-8-0038

*This information is based on the best data available at the date printed above. Please check with Romac for any updates or changes.*



www.romac.com  
21919 20th Avenue SE • Suite 100 • Bothell, WA 98021  
Phone (425) 951-6200 • 1-800-426-9341 • Fax (425) 951-6201