

STYLE 304

ALL STAINLESS STEEL SERVICE SADDLES



MATERIAL SPECIFICATIONS

SHELLS: Stainless steel per ASTM A 240, type 304, fully passivated ¹.

BOLTS: UNC rolled thread, stainless steel per ASTM A 193, type 304. Fasteners coated to prevent galling.

NUTS: Stainless steel per ASTM A 194, type 304.

WASHERS: Stainless steel per ASTM A 240, type 304 and plastic lubricating washers.

GASKET: NBR per ASTM D 2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

TAPPED OUTLET: Stainless steel per ASTM A 240, type 304.



MEETS
AWWA C800

NOM. PIPE SIZE	O.D. PIPE RANGE	304 SINGLE BOLT (not recommended for A/C pipe)				
		LENGTH	BOLT SIZE	TAP		APPROX. WEIGHT (lbs.)
				I.P. 1/2" - 1"	C.C. 3/4" OR 1"	
2"	2.13 2.38	4"	1/2"	\$84.63	\$84.63	2 #
2 1/2"	2.63 - 2.88	4"	1/2"	86.92	86.92	2 #
3"	3.00 - 3.25	4"	1/2"	88.62	88.62	2 #
	3.25 - 3.50					
	3.50 - 3.75					
	3.75 - 4.00					
4"	4.00 - 4.30	4"	1/2"	103.70	103.70	3 #
	4.50 - 4.80					
	4.80 - 5.20					
5"	5.20 - 5.60	4"	1/2"	105.00	105.00	3 #
	5.60 - 6.00					
6"	6.00 - 6.40	4"	5/8"	142.85	142.85	4 #
	6.50 - 6.90					
	6.90 - 7.30					
8"	8.00 - 8.40	4"	5/8"	144.68	144.68	5 #
	8.63 - 9.05					
	9.05 - 9.45					

¹ Passivated: Chemically treated after welding to produce a highly corrosion-resistant coating.

For easiest installation, choose the saddle with your pipe OD closest to the bottom of the range.

Other ODs available P.O.A.

TO ORDER: Use upper range when ordering. Add tap size. Be specific when ordering.

Tapped outlet products are NO CANCEL/NO RETURN items.

EXAMPLE: 304 - 4.80 x 3/4" I.P.