

305-H AND 306-H ALL STAINLESS STEEL SERVICE SADDLES



HDPE FOR HIGH DENSITY POLYETHYLENE PIPE

MATERIAL SPECIFICATIONS

Shells: Stainless steel per ASTM A 240, type 304, fully passivated ¹.

Bolts: UNC rolled thread, Teflon coated, stainless steel per ASTM A 193, type 304.

Nuts: Stainless steel per ASTM A 194, type 304.


Washers: Flat washers are stainless steel per ASTM A 240, type 304; spring washers are special "spring" grade of stainless steel and plastic lubricating washers.

Gasket: NBR per ASTM D 2000 MBC 610, compounded for water and sewer service. Other compounds available on request.

Tappped Outlet: Stainless steel per ASTM A 240, type 304.



305-H SADDLE



306-H SADDLE



Certified to NSF/ANSI 61 & 372

For above-ground HDPE applications, contact Romac's Engineering Department at 1-800-426-9341.

Products and prices listed below are standard Romac sizes. For information on other sizes, contact Romac's Engineering Department.

For important technical information on HDPE pipe, see Page 9-1 & Page 9-2.

"306-H" SADDLE

NOM. PIPE SIZE	OUTSIDE DIAMETER	TAP	I.P.	C.C.	WEIGHT (lbs.)
2"	2.13	3/4" & 1"	\$128.89	\$128.89	2 #
	2.38				
3"	3.50	3/4" & 1" 1 1/4" 1 1/2" 2"	246.39	246.39	3 #
			283.02	283.02	
			283.02	283.02	
			283.02	NA	
4"	4.50 4.80	3/4" & 1" 1 1/4" 1 1/2" 2"	253.01	253.01	4 #
			283.02	283.02	
			283.02	283.02	
			283.02	283.02	
5"	5.56	3/4" & 1" 1 1/4" 1 1/2", 2"	265.32	265.32	4 #
			310.01	310.01	
			310.01	310.01	
6"	6.63 6.90	3/4" & 1" 1 1/4" 1 1/2", 2"	295.68	295.68	4 #
			316.69	316.69	
			316.69	316.69	
8"	8.63 9.05	3/4" & 1" 1 1/4" 1 1/2", 2"	318.55	318.55	6 #
			345.81	345.81	
			345.81	345.81	

"305-H" SADDLE

NOM. PIPE SIZE	OUTSIDE DIAMETER	I.P. or C.C. 3/4", 1"	I.P. or C.C.		WEIGHT (lbs.)
			1 1/4", 1 1/2", 2"	FIP or MIP 2 1/2", 3"	
10"	10.75	\$452.80	\$494.60	\$1,003.66	14#
	11.10				
12"	12.75	452.80	494.60	1,003.66	14#
	13.20				

305-H

8" wide with four 5/8" bolts.

306-H

- (A) 2" through 5" nominal sizes with small (3/4" or 1") taps are 6" long with two 1/2" bolts.
- (B) 6" through 8" sizes with small (3/4" or 1") taps are 6" long with two 5/8" bolts.
- (C) 3" through 8" sizes with large (1 1/4", 1 1/2", or 2") taps are 8" long with two 5/8" bolts.



HDPE Products are No Cancel, No Return Items.



The 305-H and 306-H are not to be used on HDPE pipe with an SDR greater than 26.

¹ Passivated: Chemically treated after welding to produce a highly corrosive resistant coating.

TO ORDER: Use pipe O.D. when ordering. Add tap size and thread type. Be specific when ordering. Indicate if for above ground application.

EXAMPLE: 305-H - 10.75 x 3/4" I.P.

HDPE